

Product Summary



Part #	V_{DS}	$R_{DS(on).typ}$	I_D
DP023N10TGN	100V	1.75mΩ	300A

Features

- Uses advanced Trench MOSFET-DPMOS technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent $Q_g \times R_{DS(on)}$ product(FOM)
- Qualified according to JEDEC criteria

Applications

- Motor control and drive
- Battery management
- UPS (Uninterruptible Power Supplies)



100% Avalanche Tested

100% Rg Tested

Package Marking and Ordering Information

Part #	Marking	Package	Packing
DP023N10TGN	023N10TG	TOLL	Reel/Tab



Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	100	V
Continuous drain current	I_D	303	A
$T_C = 25^\circ\text{C}$ (Silicon limit)		300	
$T_C = 25^\circ\text{C}$ (Package limit)		215	
$T_C = 100^\circ\text{C}$ (Silicon limit)			
Pulsed drain current ($T_C = 25^\circ\text{C}$, t_p limited by T_{jmax})	$I_{D \text{ pulse}}$	1200	A
Avalanche energy, single pulse ($L=1\text{mH}$, $R_g=25\Omega$) ^[1]	E_{AS}	880	mJ
Gate-Source voltage	V_{GS}	±20	V
Power dissipation ($T_C = 25^\circ\text{C}$)	P_{tot}	375	W
Operating junction and storage temperature	T_j, T_{stg}	-55...+175	°C

[1].EAS is tested at starting $T_j = 25^\circ\text{C}$, $V_{GS} = 10\text{V}$.

Thermal Resistance

Parameter	Symbol	Max	Unit
Thermal resistance, junction – case.	R_{thJC}	0.4	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	45	

Electrical Characteristic (at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

Static Characteristic

Drain-source breakdown voltage	BV_{DSS}	100	-	-	V	$V_{GS}=0V, I_D=250\mu A$
Gate threshold voltage	$V_{GS(th)}$	2	3	4	V	$V_{DS}=V_{GS}, I_D=250\mu A$
Zero gate voltage drain current	I_{DSS}	-	-	1 100	μA	$V_{DS}=80V, V_{GS}=0V$ $T_j=25^{\circ}\text{C}$ $T_j=125^{\circ}\text{C}$
Gate-source leakage current	I_{GSS}	-	± 10	± 100	nA	$V_{GS}=\pm 20V, V_{DS}=0V$
Drain-source on-state resistance	$R_{DS(on)}$	-	1.75	2.1	mΩ	$V_{GS}=10V, I_D=90A$
Gate resistance	R_g	-	2	4	Ω	$V_{GS}=0V, V_{DS}=0V, f=1\text{MHz}$
Transconductance ^[2]	g_{fs}	-	167	-	S	$V_{DS}=5V, I_D=90A$

Dynamic Characteristic^[2]

Input Capacitance	C_{iss}	-	11520	-	pF	$V_{GS}=0V, V_{DS}=50V, f=1\text{MHz}$
Output Capacitance	C_{oss}	-	1541	-		
Reverse Transfer Capacitance	C_{rss}	-	67	-		
Gate Total Charge	Q_g	-	167	-	nC	$V_{GS}=10V, V_{DS}=50V, I_D=90A, f=1\text{MHz}$
Gate-Source charge	Q_{gs}	-	68	-		
Gate-Drain charge	Q_{gd}	-	34	-		
Turn-on delay time	$t_{d(on)}$	-	35	-	ns	$V_{GS}=10V, V_{DD}=50V, R_{G_ext}=2.7\Omega$
Rise time	t_r	-	43	-		
Turn-off delay time	$t_{d(off)}$	-	99	-		
Fall time	t_f	-	32	-		

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.9	1.3	V	$V_{GS}=0V, I_{SD}=90A$
Diode continuous forward current	I_S	-	300	-	A	$T_C = 25^{\circ}C$
Diode pluse current	$I_{S\ pluse}$	-	1200	-	A	$T_C = 25^{\circ}C$
Body Diode Reverse Recovery Time ^[2]	t_{rr}	-	116	-	ns	$I_F=90A, dI/dt=100A/\mu s$
Body Diode Reverse Recovery Charge ^[2]	Q_{rr}	-	345	-	nC	

[2]. Defined by design. Not subject to production test

Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3: $R_{DS(on)}$ vs Drain Current and Gate Voltage




Fig 4: $R_{DS(on)}$ vs Gate Voltage




Fig 5: $R_{DS(on)}$ vs. Temperature




Fig 6: Capacitance Characteristics




Fig 7: Gate Charge Characteristics




Fig 8: Body-diode Forward Characteristics




Fig 9: Power Dissipation




Fig 10: Drain Current Derating




Fig 11: Safe Operating Area







Fig 12: Max. Transient Thermal Impedance





Test Circuit & Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms




Package Outline: TOLL



TOP VIEW



BOTTOM VIEW



SIDE VIEW

Symbol	Common Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.40	0.09	0.09
b	0.70	0.90	0.03	0.04
b1	9.70	9.90	0.38	0.39
b2	0.40	0.50	0.02	0.02
c	0.40	0.60	0.02	0.02
D	10.28	10.58	0.40	0.42
D1	3.15	3.45	0.12	0.14
E	9.70	10.10	0.38	0.40
E1	7.90	8.30	0.31	0.33
e	1.10	1.30	0.04	0.05
H	11.48	11.88	0.45	0.47
H1	6.75	7.15	0.27	0.28
K	3.03	3.33	0.12	0.13
L	1.50	1.70	0.06	0.07
L1	0.55	0.85	0.02	0.03
L2	0.45	0.75	0.02	0.03
L3	1.00	1.30	0.04	0.05

Revision History

Revision	Major changes
1.0	Release for formal version

Intellectual Property Declaration

Where the contents disclosed in this specification involve intellectual property rights, they are the independent intellectual property rights of the company or have been licensed by the company. Without consent, no third party may use, copy or convert them, the company will pursue its legal responsibility in accordance with the law, and compensation for all the losses caused to the company.

Developer Microelectronics Confidential